


No.	CONTENT	DATE	REVISER	APPROVED
1				

- 1 BODY
- MATERIAL: AL 7075 T6
 - THICKNESS : 10T
- 2 CALBLE GLAND
- MAKER : DONG-A BESTECH
 - Explosion-proof type : At least Ex d IIC
 - IP Code : At least IP66/IP67
- MODEL NO. : A2FRC-M20b (M:M20 / F:NPT1/2)
- Size : M20xP1.5
- Tamb : At least -60°C ~ + 100°C
3. CAM SWITCH
- MAKER : ILSHIN INDUSTRIAL ELECTRIC CO.,LTD
 - Explosion-proof type : At least Ex d IIC
4. PILOT LAMP
- MAKER : ILSHIN INDUSTRIAL ELECTRIC CO.,LTD
 - Explosion-proof type : At least Ex d IIC
 - MODLE NO. : ISPL
5. Thread Standard
- Metric Thread : ISO 965-1, ISO 965-3, ISO 262
6. Surface Roughness : ISO 468

7. Screw Standard
- Hexagon Socket Head Cap Bolt : JIS B 1176
 - Round Headed Bolt : ISO 7075
 - Flat Headed Bolt : ISO 7046
8. Unspecified Screw Hole Tolerances :
- ISO 273 (Fine), ISO 286-2
9. Unspecified Tolerances : ISO 2768-n
10. Product internal Volume
- 5532 cm³

A3	<div><div><div>SUNJE</div><div>Electrostatics</div></div></div>		APPROVED	S. H. KIM	SCALE	1 / 2	UNIT	MM	TITLE : SBP-08A1EX OUTWARD				
			CHECKED	S. D. LEE									
			CHECKED	J. H. LEE	PROJECT METHOD		WEIGHT	Kg					
			DESIGN DRAWN	J. C. PARK									
									MATERIAL		-	SHEET No.	01 OF 01
									DATE		2016 / 04 / 12	DWG No.	SJ-SBP-08A1EX-A020
									FILE NAME		SJ-SBP-08A1EX-A020-OUTWARD		